
Sensor Classic A LED B22

6W 3000K Warm White 480LM


- Infra-red type sensor Classic A
- No activation during day time (when background environment brightness > 10lux)
- Suggested installation height: 2-4 metre
- 120deg detecting range
- 3.5-7.0 metre detecting range
- 60seconds activation when triggered
- Do not use lampshade
- B22 base









Order Code	65594
General Data	
Lamp Socket	B22
Design	Frosted dome
Geometric Data	
Length (mm)	101.5mm
Diameter (mm)	60mm
Weight (g)	97g
Electric Data	
Wattage	6W
Voltage	200-240 V AC
Power Factor	≥0.5
Operating Frequency	50/60 Hz
Photometric Data	
Total Luminous Flux (lm)	480
90° cone Luminous Flux (lm)	N/A
CRI	≥80
CCT	3000 K – Warm-white
Luminous Intensity (cd)	65Cd
Beam Angle (°)	220°
Lifetime	25,000 hrs
Equivalent to (W)	40W








E1703 AB57

A Group Company of MITSUBISHI CHEMICAL

Sensor Classic A LED B22

6W 3000K Warm White 480LM



Order Code	65594
Product Description	Verbatim LED Sensor Classic A B22 6W 3000K WW 480lm 220-240V

Technical Packaging Details

Giftbox Barcode	6943760255942
Inner Carton Barcode	N.A.
Outer Carton Barcode	26943760255946
Pack Dimensions (HxWxL)	126 mm x 66 mm x 66 mm
Pack Weight	130g
Carton Qty (Shipping Unit)	10
Carton Dimensions (HxWxL)	140 mm x 145 mm x 345 mm
Cartons/Layer	15
Layers/Pallet	6
Units/Pallet	900