

RHINO DC CEILING FAN

NEW PRODUCT RELEASE

Stock due: Dec 2015



Features

- 2 year in home warranty
- 5 year motor warranty
- 2.0m (79") or 2.4m (95") aluminium blades
- Energy efficient 35W DC motor
- Tropically rated
- Reversing button on remote handset to save energy in winter
- Remote controller with 6 speeds, 65K random code combinations and learning function for easy code setting included

The MERCATOR FC479009 RHINO Series is a DC ceiling fan suitable for indoor use. This ceiling fan is supplied with 6 speed remote controller

All MERCATOR ceiling fans comply with relevant Australia Safety Standards.

Features

- 2 year in home warranty
- 5 year motor warranty
- 2.0m (79") or 2.4m (95") aluminium blades
- Energy efficient 35W DC motor
- Tropically rated
- Reversing button on remote handset to save energy in winter
- Remote controller with 6 speeds and learning function for easy code setting included



Product Specifications

Colour/Finish option	Brushed Chrome, White
Blade	9 x aluminium blades
Blade colour	Black / White
Blade pitch	11°
Rated input voltage	230-240V~
Rated input frequency	50Hz
Motor power rating	DC 35W _{max}
Lamp power rating	n/a
Gross weight	8.7kg (body), 4.4kg (2m blade), 5.4kg (2.4m blade)
Net weight	7.3kg (body), 4.0kg (2m blade), 5.0kg (2.4m blade)
Packaging	Colour box (body), Plain box (blades)
Packaging size (mm)	570 x 385 x 238mm (body)
Packaging size (mm)	1035 x 90 x 75mm (2m blades)
Packaging size (mm)	1235 x 90 x 75mm (2.4m blades)

Bar Codes & TUN Numbers

Description	SKU Model	Bar Code	TUN Number
Motor Body	FC479009BC	9312699176043	(01)19312699176040
Motor Body	FC479009WH	9312699176425	(01)19312699176422
2.0m blades	FC47920LBK	9312699176050	(01)19312699176057
2.0m blades	FC47920LWH	9312699176074	(01)19312699176071
2.4m blades	FC47924LBK	9312699176067	(01)19312699176064
2.4m blades	FC47924LWH	9312699176081	(01)19312699176088

Performance**

SPEED	1	2	3	4	5	6
2.0m RPM	31	41	51	61	71	85
2.4m RPM	31	36	42	48	54	61

*This Product must be installed by a licensed electrician

**Actual performance may vary.